

Trolley designed for quick winch installation & removal.



SPIDER LIFT WINCH

MODEL	MRC (kg)	Length of Cable (m)	Max Hoisting speed (m/min')	Rope Diam. (mm)	Weight (Kg)
MONITOR 2095	250	25	28	6	83
MONITOR 2210					
MONITOR 2714	250	25	28	6	69
MONITOR 30T					
MONITOR 3315	250	40	18	6	86
MONITOR 43T	500	40	18	6	86

Approved according to uni-EN13.000 & winch 4301/1 and AS 1418.5-2013

The spider-type tracked platform is synonymous with equipment that provides great versatility.

This concept has made it possible to create a lifting accessory that is particularly suitable for light loads as an alternative to the operator basket. The simplicity of coupling and release the aerial basket together with the remote control of the "RADIO" type allowed the Platform Basket technicians to implement a hoisting winch of extremely compact dimensions, which is fully hydraulic, controlled at a distance and with a quantity of cable that allows easy handling of materials on roofs, floors of buildings and in any situation at a height.

The device is composed of a pre-assembled winch kit with all the safety devices in conformity with the Australian standard AS1418.5-2013, that through a simple coupling pin allows the platform to recognise the device and therefore allow its safe use.

The winch comes with its own compact wheeled trolley. After removing the basket from the spider lift, one operator can easily wheel the trolley into position and quickly connect the winch to the machine with its quick couplings.

The radio-type remote control will provide the operator with excellent visibility in handling, which is equivalent to a lifting crane.