

PB43T/400 43M

Cherry Picker Specification Guide



PERTH PICKER HIRE THE TRACK MOUNTED SPECIALIST

ABOUT PB43T/400

With a massive 43 m of working height, and over 18 m of horizontal outreach, the new Monitor 43T Spider Lift is truly a formidable weapon. With a basket capacity of 400 kg, this machine has the ability to tackle the biggest jobs where size really does matter!

Enormous stabilizer leg travel allows the Monitor 43T to set up and operate in the most challenging terrain. The Monitor 43T's powerful track drive will ensure it gets to the location with ease.



PB43T/400 SPECIFICATIONS

Max Working Height

43.18m

Max Working Height

in Narrow Set

40.50m

Max Horiz Outreach

18.69m

Max Rated Capacity

400kg

Weight: Engine + Lithium Batteries

LBD 12920kg

Turret Rotation

Continuous 360°

Basket Rotation

180°

Ground Pressure Driving

92.35kN/m²

Max Stabiliser Force

94kN

Max Stabiliser Pressure (std Foot Pad)

93.6kN/m²

Tracks Retracted

1.99m High

Traffic Load (Live Load) Travelling

6.0kN/m²

Traffic Load (Live Load) Stabilised Wide

4.2kN/m²

Traffic Load (Live Load)

Stabilised Narrow

4.9kN/m²

Auto Levelling

Std

Max Slope for Stabilisers

(No Extra Pads)

25°

Gradeability Lengthwise

15°

Gradeability Sideways

17°

Standard Engine

Kubota 37Hp Diesel

Dual Power Options

Lithium Batteries

Expanding Tracks

Std

Max Drive Speed

1.5km/h

Radio Control

Std

Electric Emergency

Lowering


Std


Hydraulic Winch

Optional

PERTH PICKER HIRE THE TRACK MOUNTED SPECIALIST

PB43T/400 TECHNICAL DRAWINGS





8400

